

## BWS Waterproof Weight Indicator

### General Specifications

- Display 52mm digit LCD display, with white LED backlight
- Keyboard 7 keys (Mechanical switch)
- Housing Stainless steel
- Max. Divisions 6,000e; 30,000d
- Load cell excitation voltage 5V/150mA
- ADC update  $\leq 1/10$  second
- Operating Temp.  $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Power AC adapter (12V/500mA), rechargeable battery (6V/4Ah)
- Gross weight 3.2kg
- Packing Master carton holds 4, dimension 0.093m<sup>3</sup>



IP65

- Easy to use, front panel configuration
- Applications: 1. Zero 2. Accumulation 3. Check weighing 4. Net/gross shift 5. Weighing unit conversion 6. Weight hold function (non OIML version only) 7. Animal weighing
- OIML approval from DELTA (approval no.DK0199.165)
- IP65 waterproof rating
- 1.2" LED display available (BWS-E)
- Optional RS-232 interface, Blue tooth
- Optional analogue output (0-10V/4-20mA)
- Optional setpoint output (HI/OK/LOW/BEEP)





## BWS Waterproof Weight Indicator

Model Number	Capacity	Readability	Division	Approx. weight	Approval
BWS	X	X	30,000d	2.0kg	CE
BWS-M	X	X	6,000e	2.0kg	CE, OIML
BWS-E	X	X	30,000d	3.2kg	CE

### Options



### Dimensions(mm)



### Print formats

