

## DFWL

"DFWL": MULTIFUNCTION WEIGHT INDICATOR



High performance and reliability at a competitive price. The DFWL digital weight indicator is versatile and easy to programme and use. The wide range of available functions and interfaces, make it suitable for many different kinds of industrial and commercial weighing applications. Suitable for pallet truck scales, fork lifts and automotive. Standard fitted with a support bracket with adjustable inclination, for use on the table, column, or wall. CE-M approvable (OIML R-76 / EN 45501).

Working in cooperation with:



The best solution  
for advanced industrial  
applications

## MAIN FEATURES:

- Weight indicator with ABS case, 25mm backlit LCD display with 6 high contrast digits and icons for showing the active functions. 5-key functional waterproof keypad.
- Easy to clean ABS IP54 case, resistant to harsh and corrosive environments.
- Suitable for use on the table, column, or wall.
- Fitted with fixing bracket with adjustable inclination.
- A/D 24 bit, 4 channel converter, max. 200 conv./sec. autoselect, and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3  $\mu$ V/e in CE-M approved versions for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each.
- Digital calibration and Set-Up from keypad or from PC through DINITOOLS.
- Power supply from 5 to 12Vdc. EU, UK, US, AU plugs included as standard.
- Power supply: 12V power unit included (if connected it excludes the battery supply) or 4 AA batteries (not included), operating time up to 40 hours.

## MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- Australian legal for trade certificate of approval (NMI S788)

## I/O SECTION

- RS232/C bidirectional port on RJ11 connector for quick connection on screw terminal, configurable for PC, PLC, or additional remote display.

## AVAILABLE LANGUAGES FOR PRINTING

- IT, EN, FR, DE, ES, PT, CN\*, EL\*

\* For Chinese and Greek a programming of the printer/labeler is required (S1, only at the time of order)

## SELECTABLE FUNCTION MODES

- The user can select the operating modes directly using the dedicated key\*:
  - High resolution display x 10
  - Precision weighing with temporary recalibration via a sample weight (for internal factory use)
  - Net/Gross
  - Lb to Kg converter
  - Free conversion factor (for meter and litre counters etc.)
  - Weight totalizer
  - Formulizer
  - +/- controller with quick target and threshold input
  - Percentage weighing
  - Piece counter
  - Hold

The "alibi memory" function is available in combination with the required operating mode and it is activated automatically when installing the relevant optional board.

- Optional functions:
  - PEAK, detection of weight peaks (code DFWPK)
  - Newton to Kg converter (code DFWPK)
- Access to the user menu is gained using the dedicated key\* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.

*\* These quick access keys to the menus can be blocked by configuring a dedicated password.*



[www.diniargeo.com](http://www.diniargeo.com)

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano - Modena - Italy  
Tel. +39.0536 843418



**Maximus Scales NZ Ltd**

17 Hyland Crescent - Rotorua - 3015  
+64 27 273 6864  
[jamie.bartlett@maximus-scales.co.nz](mailto:jamie.bartlett@maximus-scales.co.nz)

SALES AND TECHNICAL ASSISTANCE SERVICE